

AirLive IP Camera Family (2011)

AirLive IP Camera family (2011)

Wired
outdoor



POE-250HD



OD-600HD



OD-325HD



OD-2025PHD



OD-2025HD

Wireless
indoor



WL-2000CAM



WL-2600CAM



WN-150CAM



WL-350HD



WN-2600HD



WN-200HD

Wired
indoor



POE-100CAM v2



IP-150CAM



POE-200CAM v2



POE-260CAM



POE-100HD



POE-100HD-ICR



POE-200HD



POE-2600HD



IP-200PHD

VGA

1.3 M pixel

2 M pixel








AirLive IP Camera 2 M pixel specs (1)

Model	IP-200PHD	WN-200HD	POE-2600HD	WN-2600HD	OD-2025PHD	OD-2025HD	OD-2050HD	OD-2060HD
Picture								
Image Sensor	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS
Max Resolution	1600 X 1200	1600 X 1200	1920 X 1080	1920 X 1080	1920 X 1080	1920 X 1080	1920 X 1080	1920 X 1080
	UXGA	UXGA	1080P	1080P	1080P	1080P	1080P	1080P
	15FPS	15FPS	30FPS	30FPS	30FPS	30FPS	30FPS	30FPS
Compression	MJPEG	MJPEG	MJPEG	MJPEG	MJPEG	MJPEG	MJPEG	MJPEG
	MPEG4	MPEG4	MPEG4	MPEG4	MPEG4	MPEG4	MPEG4	MPEG4
	H.264	H.264	H.264	H.264	H.264	H.264	H.264	H.264
Max Frame Rate	30	30	30	30	30	30	30	30
Lens	4.3mm	4.3mm	f:4.3mm / F:1.8	f:4.3mm / F:1.8	4 mm	4 mm	2.7- 9 mm	f:4.3mm / F:1.8
Digital Zoom	V	V	V	V	V	V	V	V
	Free Scale							
Motion Detection	V	V	V	V	V	V	V	V
	10 windows	10 windows	10 windows	10 windows	10 windows	10 windows	10 windows	10 windows
NightVision LED			V	V	24 IR LED	24 IR LED	V	
			15m	15m	25m	25m	10m	
Mechanical IR-cut Filter			V	V	V	V	V	V

AirLive IP Camera 2 M pixel specs (2)

Model	IP-200PHD	WN-200HD	POE-2600HD	WN-2600HD	OD-2025PHD	OD-2025HD	OD-2050HD	OD-2060HD
Picture								
Pan/Tilt Control			355 pan / 100 tilt	355 pan / 100 tilt				355 pan / 100 tilt
Vandal Proof							V	V
Outdoor Use					IP66	IP66	IP66	IP66
PoE (802.3af)			V			V	V	V
Passive PoE	V				V			
Wireless (IEEE 802.11)		V 11b/g/n		V 11b/g/n				
2-WAY Audio	V	V	V	V	V	V	V	V
Audio Output Port	V	V	V	V	V	V	V	V
Audio Input Port					V	V	V	V
Built-in Mic	V	V	V	V				
Onvif	V	V	V	V	V	V	V	V
Memory Card Slot	Micro SD	Micro SD	Micro SD	Micro SD				
Digital Input			1	1	1	1	1	1
Digital Output			1	1	1	1	1	1
Application Environment	Home Office	Home Office	Lobby Office Indoor Parking	Lobby Office Indoor Parking	Outdoor Parking Indoor Parking Street Patrol	Outdoor Parking Indoor Parking Street Patrol Stairway	Bank Factory Super Market Shopping Mall	Bank Factory Super Market Shopping Mall

AirLive IP Camera 1.3 M pixel specs (1)

Model	OD-600HD	POE-200HD	OD-325HD	POE-250HD	WL-350HD	PoE-100HD	PoE-100HD-ICR
Picture							
Image Sensor	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS
Max Resolution	1280 X 1024	1280 X 1024	1280 X 1024	1280 X 1024	1280 X 1024	1280 X 1024	1280 X 1024
	SXVGA	SXVGA	SXVGA	SXVGA	SXVGA	SXVGA	SXVGA
	15FPS	15FPS	15FPS	15FPS	15FPS	15FPS	15FPS
Compression	MJPEG	MJPEG	MJPEG	MJPEG	MJPEG	MJPEG	MJPEG
	MPEG4	MPEG4	MPEG4	MPEG4	MPEG4	MPEG4	MPEG4
	H.264	H.264	H.264	H.264	H.264	H.264	H.264
Max Frame Rate	30	30	30	30	30	30	30
Lens	f:4.3mm / F:1.8	f:4.3mm / F:1.8	f:4-9mm / F:1.8	f:4.3mm / F:1.8	f:4.2mm / F:1.8	f:4.3mm / F:1.8	f:4.3mm / F:1.8
Digital Zoom	V	V	V	V	V	V	V
	Free Scale Zoom				10X Digital Zoom	Free Scale Zoom	Free Scale Zoom
Motion Detection	V	V	V	V	V	V	V
	10 windows	10 windows	10 windows	10 windows	10 windows	10 windows	10 windows
NightVision LED			24 IR LED		6 White LED		
			25m		5m		
Mechanical IR-cut Filter	V		V				V

AirLive IP Camera 1.3 M pixel specs (2)

Model	OD-600HD	POE-200HD	OD-325HD	POE-250HD	WL-350HD	PoE-100HD	PoE-100HD-ICR
Picture							
Pan/Tilt Control	355 pan / 125 tilt						
Vandal Proof	V			V			
Outdoor Use	IP65		IP66	IP66			
PoE (802.3af)	V	V	V	V		V	V
Passive PoE							
Wireless (IEEE 802.11)					V 11b/g		
2-WAY Audio	V	V	V	V	V	V	V
Audio Output Port	V	V	V	V	V	V	V
Audio Input Port	V	V	V	V			
Built-in Mic					V	V	V
Onvif							
Memory Card Slot							
Digital Input	1	1	1	1		1	1
Digital Output	1	1	1	1		1	1
Application Environment	Outdoor Parking Factory Driveway Entrance	Elevator Hotel Hallway Shopping Mall	Outdoor Parking Indoor Parking Street Patrol Stairway	Bank Factory Super Market Shopping Mall	Home Office	Entrance Hallway Shopping Area Cashier	Entrance Hallway Shopping Area Cashier

AirLive License Software



CamPro Professional

Campro Professional vs. Campro Express 64v2

	Campro Professional	Campro Express 64v2
Number of Channels	64	64
Client/Server	Yes	No
Camera Tempering Detection	Yes	Yes
Video Analytic	<ul style="list-style-type: none"> ●Smart Motion ●Object Loss ●Foreign Object ●Trip Wire ●Object Counting ●Face Counting 	No
Image Enhancement	Yes	No
E-Map	Unlimited	2-Level
CMS Lite	Yes (256 Channels)	No
Muti-Monitor Support	5 Monitors	2 Monitors
Camera Supports	More than 30 brands	AirLive, AXIS, Sony, Vivotek
Licensing	Purchase by channels, USB Keypro protect	Free

Examples: Object Counting

Object Counting let store owners to calculate the number of customers in and out of the stores. You can choose one direction or both direction for counting. The number can be display on screen and saved to a database file.



Face counting allows you to keep track of the number of people at a particular location.



Examples: Image Enhancement

Image enhancement can improve the visibility of your video image. It can be applied during recording or playback.



The CamPro Professional comes with a bundle CMS lite application to central manage up to 256 channels of camera from your NVR or Campro Professional Installations. It is a perfect solution for franchise stores or branch offices.

CamPro Professional



NVR



NVR



CMS Lite

AirLive POE switches

Model	POE-FSH2422G-390	POE-FSH2422G-250	POE-FSH1608	POE-FSH804	POE-FSH8PW
POE Standard	802.3af 48Volt	802.3af 48Volt	802.3af 48Volt	802.3af 48Volt	24V Passive PoE
PoE Ports	24	24	8	4	8
10/100 Port	24	24	16	8	8
Gigabit Port	2	2	0	0	0
SFP Gigabit Fiber	2	2	0	0	0
Web Managed	Yes	Yes	No	No	Yes
Total Power	390W (Full Power to all 24 ports)	250W	120W	55W	130W
Cabling Distance	100m	100m	100m	100m	100m
Power Adapter	Internal	Internal	External	External	Internal
Application	IPCAM, AP	IPCAM, AP	IPCAM, AP	IPCAM, AP	Passive PoE AP/CPE
Supported AirLive Models	AirLive 802.3af (48V) PoE IPCAMs, A.DUO, WL-5470POE, N.TOP				<ul style="list-style-type: none"> • 24V PoE Devices: IP-200PHD-24 and IP-200PHD-24B • 12-24V PoE Devices : G.DUO, AP60, AirMax2, AirMax5
Availability	Nov, 2011	Nov, 2011	Now	Now	Nov, 2011