


SPECIFICATION

Drop cable for FTTx.Aerial application.Flat type

Application

- 1.Adopted to outdoor level and vertical distribution.
- 2.Suitable for connect with communication equipment.
- 3.Long distance and local area network communication.

(31241) F. CABO DROP 2 FIBRAS G657A2 PP SM 2KM M.METAL



ITEM		CONSTRUCTION
FIBER COUNT		2
fiber color		blue , orange
CABLE DIAMETER		2.0±0.15mm*5.0mm±0.3mm
CABLE WEIGHT		18KG/KM ±2

Cable's Outer jacket color

black

Cable construction details

Items	Description	
Number of fiber	2cores	
Fiber type	G657A2	
Messenger	Material	steel wire
	Diameter	1.0mm
Strength member	Material	steel wire
	Diameter	0.5mm±0.05mm
Outer sheath	Material	LSZH
	Diameter	2.0±0.15mm*5.0mm±0.3mm

Cable Mechanical characteristic

Items	Cable Diameter	Weight(kg/km)
2cores	2.0±0.15mm*5.0mm±0.3mm	18±2
Installation Temperature range	.-15--+80 °C	
Operation and transport temperature	.-20--80 °C	
Storage temperature	.-20--+80 °C	
Tensile strength (N)	Long term	300N
	Short term	700N
Crush load (N/100mm)	Long term	1000N
	Short term	2200N
Min Bending Radius(mm)	Dynamic	30D mm
	Static	15D mm