

---

## FD600-104 series EPON ONU(Includes Wi-Fi series)



### Brief Views

FD600-104 series is C-Data's for broadband access market based on the introduction of EPON technology passive optical network terminal products. It's with EPON OLT are used together to provide a complete broadband access solution.

EPON technology is a kind of emerging technology which takes advantage of PON technology and Ethernet technology also is a kind of point to multi-point network technology. OLT through the passive optical network to connect multiple ONU with single fiber bidirectional technical can rarely used fiber resources to meet the operators of the multi-user access requirements.

FD600-104 series fully meet IEEE802.3ah and CTC3.0 standard protocol. It has good third-party compatibility to work with the third party OLT, It supports 1Gbps transmission rate up and down and provides users with good QOS, flexible bandwidth allocation of Ethernet services and IP integrated service.


FD600-104 series can integration wireless function with meet 802.11 n/b/g technical standards, It has built-in high gain directional antenna, the wireless transmission rate up to 300Mbps. It has the characteristics of strong penetrating power and wide coverage. It can provide users with more efficient data transmission security.


### Functional Feature

- Support port-based rate limitation and bandwidth control;
- In compliant with IEEE802.3ah Standard

- Wi-Fi series meet 802.11 n/b/g technical standards
- Up to 20KM transmission Distance
- Support data encryption, group broadcasting, port Vlan separation ,etc.
- Support Dynamic Bandwidth Allocation (DBA)
- Support ONU auto-discovery/Link detection/remote upgrade of software;
- Support port mode of VLAN configuration
- Support power-off alarm function ,easy for link problem detection
- Support broadcasting storm resistance function
- Support port isolation between different ports
- Support port flow control
- Support ACL and SNMP to configure data packet filter flexibly
- Specialized design for system breakdown prevention to maintain stable system
- Support software online upgrading
- EMS network management based on SNMP ,convenient for maintenance

**Product interface and LED definitions ( Wi-Fi type example)**





Indicator		Description	
1	PWR	Power status	On: The ONU is power on; Off: The ONU is Power off;
2	PON	ONU Register	On: Success to register to OLT Blinking: In process of registering to OLT; Off: In process of registering to OLT;
3	LOS	EPON optical signals	On: Optical power lower than receiver sensitivity ; Off: Optical in normal
4	LANn	LAN Port status	On: Ethernet connection is normal; Blinking: Data is being transmitted through the Ethernet port; Off: Ethernet connection is not set up;
5	WIFI	WIFI	Blinking : Data is being transmitted On : Wi-Fi function Opens

## Specification

Item	Parameter
PON Interface	1 EPON optical interface Meet 1000BASE-PX20+ standard Symmetric 1.25Gbps upstream/downstream SC single-mode fiber split ratio: 1:64 Transmission distance 20KM
User Ethernet Interface	4*10/100M or 4*10/100/1000M auto-negotiation Full/half duplex mode RJ45 connector Auto MDI/MDI-X 100m distance
Power Interface	12V DC Power supply An external 12V 0.5A AC/DC power supply adapter
PON Optical Parameter	Wavelength: Tx 1310nm, Rx1490nm Tx Optical Power: 0~4dBm Rx Sensitivity: -27dBm Saturation Optical Power: -3dBm Connector Type: SC Optical Fiber: 9/125µm single-mode fiber
Data Transmission	PON Throughput: Downstream 950Mbps; Upstream 930Mbps

Parameter	Ethernet: 100Mbps or 1000Mbps Packet Loss Ratio: <math>1 \times 10^{-12}</math> latency: <math>1.5\text{ms}</math>
Business Capability	Layer 2 wire speed switching Support VLAN TAG/UNTAG, VLAN conversion Support Port-based speed limitation Support Priority classification Support storm control of broadcast Support loop detection
Network Management	Support IEEE802.3 QAM, ONU can be remotely managed by OLT Support Remote management through SNMP and Telnet Local management
Management Function	Status monitor, Configuration management, Alarm management, Log management
Shell	Plastic casing
Power	4FE: <math>4.2\text{W}</math>, 12V/0.5A power supply adapter 4FE+WIFI: <math>5.2\text{W}</math>, 12V/0.5A power supply adapter 4GE: <math>6\text{W}</math>, 12V/1A power supply adapter 4GE+WIFI: <math>7\text{W}</math>, 12V/1A power supply adapter
Physical Specifications	Item Dimension: 160mm(L) x 120mm(W) x 32.5mm (H) Item weight: 0.2kg
Environmental Specifications	Operating temperature: 0 to 50°C Storage temperature: -40 to 85°C Operating humidity: 10% to 90%(Non-condensing) Storage humidity: 10% to 90%(Non-condensing)

## WIFI Specification (Suitable for the WIFI devices)


	Item	Parameter
<b>Performance parameters</b>	Operating Mode	Router or bridge
	Throughput	IEEE 802.11b: 11Mbps
		IEEE 802.11g: 54 Mbps
		IEEE 802.11n: 300Mbps
	Frequency	2.412 ~ 2.472 GHz
	Channel	13*Channel, configurable to meet the standard of USA, Canada, Japan and China
	Modulation	DSSS , CCK and OFDM
Coding	BPSK, QPSK, 16QAM and 64QAM	
RF receive sensitivity	802.11b: -82dBm @ 1 Mbps; -80dBm @ 2 Mbps; -78dBm @ 5.5 Mbps; -76dBm @ 11 Mbps	

		802.11g: -82dBm @ 6 Mbps; -81dBm @ 9 Mbps; -79dBm @ 12 Mbps; -77dBm @ 18 Mbps; -74dBm @ 24 Mbps; -70dBm @ 36 Mbps; -66dBm @ 48 Mbps; -65dBm @ 54 Mbps
	RF output level	802.11b: 16.5 ±1dBm 802.11g: 13 ± 1dBm @ 54 Mbps; 14 ± 1dBm @ 48 Mbps; 15 ± 1dBm @ 6 ~ 36 Mbps 802.11n: 13 ± 1dBm @ 54 Mbps; 14 ± 1dBm @ 48 Mbps; 15 ± 1dBm @ 6 ~ 36 Mbps
	Encryption Mode	802.11i security: WEP-64/128, TKIP (WPA-PSK) and AES (WPA2-PSK)

## Network application

Typical Solution: FTTH, FTTO

Typical Business: INTERNET, IPTV, VOD, IP Camera, WIFI



**Figure: FD600-104 Application Diagram**

 **Ordering Information**

Product Name	Product Model	Descriptions
4FE	FD600-104F-HR122	4*10/100M Ethernet interface, 1 EPON interface, plastic casing, external power supply adapter
4GE	FD600-104G-HR122	4*10/100/1000M Ethernet interface, 1 EPON interface, plastic casing, external power supply adapter
4FE+WIFI	FD600-104FW-HR122	4*10/100M Ethernet interface, support Wi-Fi function, 1 EPON interface, plastic casing, external power supply adapter
4GE+WIFI	FD600-104GW-HR122	4*10/100/1000M Ethernet interface, support Wi-Fi function, 1 EPON interface, plastic casing, external power supply adapter