

## DS-3E0526P-E/M 24-Port Gigabit Unmanaged PoE Switch

DS-3E0526P-E/M switch is a layer 2 PoE network switch, providing 24 × Gigabit PoE ports and 2 × Gigabit SFP fiber optical ports. On top of high-performance access, the switch provides advanced PoE power technology to guarantee the stable network upload of the adaptive data.



### Feature and Function


- 24 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports.
- IEEE 802.3at/af standard.
- IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standard.
- 6 KV surge protection for PoE ports.
- PoE power management.
- Gigabit network access.
- Wire-speed forwarding.
- Store-and-forward switching.
- Solid high-strength metal shell.

## Specification


Model		DS-3E0526P-E/M
Network parameters	Port number	24 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports
	Port type	RJ45 port, full duplex, MDI/MDI-X adaptive
	Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3z
	Forwarding mode	Store-and-forward switching
	MAC address table	8 K
	Switching capacity	52 Gbps
	Packet forwarding rate	38.688 Mpps
	Internal cache	4.1 Mbits
PoE power supply	PoE standard	IEEE 802.3af, IEEE 802.3at
	PoE power pin	Ethernet cable 1/2/3/6 provide power supply.
	PoE port	Ports 1 to 24
	Max. port power	30 W
	PoE power budget	225 W
	Max. power consumption	250 W
General	Shell	Metal material with a fan equipped.
	Net weight	2.920 kg (6.44 lb)
	Gross weight	4.120 kg (9.08 lb)
	Dimension (L × H × D)	440 mm × 44 mm × 220.8 mm (17.3" × 1.7" × 8.7")
	Operating temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating humidity	5% to 95% (no condensation)
	Storage humidity	5% to 95% (no condensation)
	Power supply	100 to 240 VAC, 50/60 Hz, 4 A (Max)
	Power consumption in idle	25 W

## Physical Interface

Front panel:



Back panel:



## Available Model

DS-3E0526P-E/M


## Optional Accessory

SFP Module	Fiber type	Connector	Date Rate	Wavelength	Distance
HK-SFP-1.25G-20-1310	Single fiber, Single-mode	LC	1250 Mbps	Tx1310nm/Rx1550nm	0 to 20 km
HK-SFP-1.25G-20-1550	Single fiber, Single-mode	LC	1250 Mbps	Tx1550nm/Rx1310nm	0 to 20 km
HK-SFP-1.25G-1310-DF-MM	Duplex fiber, Multi-mode	LC	1250 Mbps	Tx1310nm/Rx1310nm	0 to 1 km
HK-SFP-1.25G-20-1310-DF	Duplex fiber, Single-mode	LC	1250 Mbps	Tx1310nm/Rx1310nm	0 to 20 km


### NOTE

HK-SFP-1.25G-20-1310 has to work with HK-SFP-1.25G-20-1550 as a pair.

**Dimension (unit: mm)**



## Typical Application



Distributed by

