


FC-6S


High-precision fiber cleaver



36000 times
blade life



3-in-1
universal holder



≤ 1.5 degree
Cleaved angle



Product Features

- Blade life up to 36,000 times
- Suitable for various optical fibers of 0.25~3.0mm
- High-precision CNC machining and forming, excellent texture
- Typical cutting angle ≤ 1.5 degree
- Tungsten steel blade, wear resistance, high hardness, corrosion resistance
- Traditional bench top design, simple and easy to use



Product selling point



Pressure pad

Silicone pressure pad can effectively hold down the optical fiber




Holder

All-in-one fixture suitable for various optical fibers of 0.25~3.0mm



Blade

Real tungsten steel blade, wear resistance, high hardness, corrosion resistance






Slide

High-precision slide, open the cover will return automatically



3-in-1 holder



Products Showing





Product parameter

Fiber Material	Single fiber
Cladding Diameter	125μm
Cleaved Length	Single fiber: 8~20mm / Ribbon fiber: 10mm
Applicable Fiber Cable	Single fiber: 250μm, 900μm, 3.0mm / flat cable / Ribbon fiber: 2 to 12 fiber cable
Typical Cleaved Angle	Less than 1.5 Degrees ★①
Typical Blade Life	Total 36,000 fiber cleaves (replaceble) ★②
Off-cut Collector	Pre-fitted
Type of Offcut Bin	Manual
Auto Return	Pre-fitted
Dimension / Weight	63*76*63 (mm)/ 267g

★① The fiber cleave angle changes by operating environment

★② Blade life changes by operating environment