

# EchoLife HS8546V5 Datasheet

EchoLife HS8546V5, an intelligent routing-type ONT

## Overview



## Device Parameters

<b>Dimensions (H x W x D) (without external antenna and pads)</b>	25 mm x 153 mm x 120 mm (without external antenna and pads)	<b>System power supply</b>	11–14 V DC, 1.5A
<b>Weight</b>	About 250 g	<b>Static power consumption</b>	5.3 W
<b>Operating temperature</b>	0°C to 40°C	<b>Maximum power consumption</b>	18 W
<b>Operating humidity</b>	5% RH to 95% RH (non-condensing)	<b>NNI</b>	GPON
<b>Power adapter input</b>	100–240 V AC, 50/60 Hz	<b>UNI</b>	1POTS + 4GE + 2.4G/5G Wi-Fi+ 1USB
<b>Indicators</b>	Power/PON/LOS/LAN/TEL/USB/WLAN/WPS	<b>Optical Connector</b>	SC/APC

# Interface Parameters

<p><b>GPON port</b></p> <ul style="list-style-type: none"> <li>• Class B+</li> <li>• Receiver sensitivity: -27dBm ~ -29dBm</li> <li>• Overload optical power: -8 dBm</li> <li>• Wavelengths: US 1310nm, DS 1490nm</li> <li>• Wavelength blocking filter (WBF) of G.984.5</li> <li>• Flexible mapping between GEM Port and TCONT</li> <li>• GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>• Bi-directional FEC</li> <li>• SR-DBA and NSR-DBA</li> <li>• Type B (single-homing&amp;dual-homing)</li> </ul>	<p><b>POTS port</b></p> <ul style="list-style-type: none"> <li>• Maximum REN: 4</li> <li>• G.711A/μ, G.729a/b, and G.722 encoding/decoding</li> <li>• T.30/T.38/G.711 fax mode</li> <li>• DTMF</li> <li>• Emergency calls (with the SIP protocol)</li> </ul>
	<p><b>USB port</b></p>
<p><b>Ethernet port</b></p> <ul style="list-style-type: none"> <li>• Ethernet port-based VLAN tags and tag removal</li> <li>• 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>• QinQ VLAN</li> <li>• Limit on the number of learned MAC addresses</li> <li>• MAC address learning</li> <li>• Auto-adaptive 10 Mbit/s, 100 Mbit/s or 1000 Mbit/s</li> <li>• Interoperable with 3<sup>rd</sup> party device.</li> </ul>	<p><b>WLAN</b></p> <ul style="list-style-type: none"> <li>• IEEE 802.11 b/g/n (2.4G)</li> <li>• IEEE 802.11 a/n/ac (5G)</li> <li>• 2 x 2 MIMO (2.4G&amp;5G)</li> <li>• Antenna gain: 5 dBi</li> <li>• WMM/Multiple SSIDs/WPS</li> <li>• 2.4G&amp;5G concurrent</li> <li>• Air interface rate:300 Mbit/s (2.4G); 867 Mbit/s(5G)</li> </ul>

# Product Function


<p><b>Smart interconnection</b></p> <ul style="list-style-type: none"> <li>• Smart Wi-Fi coverage</li> <li>• SIP/H.248 auto-negotiation</li> <li>• Any port any service</li> <li>• Parental control</li> <li>• L2/L3 (IPv4) forwarding: 1G uplink, 2G downlink</li> </ul>	<p><b>Smart O&amp;M</b></p> <ul style="list-style-type: none"> <li>• IPTV video quality diagnosis</li> <li>• eMDI</li> <li>• Rogue ONT detection and isolation from the OLT</li> <li>• Call emulation, and circuit test and loop-line test</li> <li>• PPPoE/DHCP simulation testing</li> <li>• WLAN emulation</li> </ul>	<p><b>Layer 3 features</b></p> <ul style="list-style-type: none"> <li>• PPPoE/Static IP/DHCP</li> <li>• NAT/NAPT</li> <li>• Port forwarding</li> <li>• ALG, UPnP</li> <li>• DDNS/DNS server/DNS client</li> <li>• IPv6/IPv4 dual stack, DS-Lite and IPv6 SPI</li> <li>• Static/Default routes</li> <li>• Multiple services on one WAN port</li> </ul>	<p><b>Security</b></p> <ul style="list-style-type: none"> <li>• SPI firewall</li> <li>• Filtering based on MAC/IP/URL addresses</li> <li>• Support WEP, 128-bit WEP, WPA2-PSK, WPA-PSK, WPA.</li> </ul> <p><b>Common O&amp;M</b></p> <ul style="list-style-type: none"> <li>• OMCI/Web UI/TR069</li> <li>• Variable-length OMCI messages</li> <li>• Dual-system software backup and rollback</li> </ul>
<p><b>Multicast</b></p> <ul style="list-style-type: none"> <li>• IGMP v2/v3 proxy/snooping</li> <li>• MLD v1/v2 snooping</li> </ul>	<p><b>Smart service</b></p> <ul style="list-style-type: none"> <li>• Scheduled Wi-Fi shutdown</li> <li>• Smart Wi-Fi sharing: Portal/802.1x authentication</li> </ul>	<p><b>Power saving</b></p> <ul style="list-style-type: none"> <li>• Indicator power saving</li> <li>• COC V5</li> </ul>	<p><b>QoS</b></p> <ul style="list-style-type: none"> <li>• Ethernet port rate limitation</li> <li>• 802.1p priority</li> <li>• SP/WRR/SP+WRR</li> <li>• Broadcast packet rate</li> </ul>

	SoftGRE-based sharing		limitation
--	-----------------------	--	------------

**Copyright © Huawei Technologies Co., Ltd. 2020. All rights reserved.**

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

**Trademarks and Permissions**

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

**Notice**

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

**Huawei Technologies Co., Ltd.**

Address:Huawei Industrial Base Bantian,  
Longgang Shenzhen 518129 People's  
Republic of China

Website:<http://www.huawei.com>