


TLS-35

Optical Light Source



Product Characteristics

- 2.5mm universal interface + SC Adaptor
- Typical output power: -5dB
- SM wavelengths 1310nm/1550nm
- MM wavelengths 850nm/1300nm
- SM&MM 850nm/1300nm/1310nm/1550nm
- PON wavelengths 1310nm/1490nm/1550nm
- Silicon shell protection design, drop proof 2m
- LED backlight function, can work in dark environment



Backlight display



One-key start



Automatic shutdown



Plug and play



Super long standby



Silicone protective case



Main Features



Drop protection



Mini Size



Bracket design



Detachable protective sleeve

TLS-35



Interface accessory



SC



FC



ST

Wavelength(nm)	1310+1550nm (TLS-35-S)
	850+1300nm (TLS-35-M)
	850+1300+1310+1550nm (TLS-35-MS)
	1310+1490+1550nm (TLS-35-PON)
Typical Output Power	-5dB
Optical Connector	SC+2.5mm universal (1.25mm for LC is Optional)
Power Supply	Alkaline Battery(3 AA 1.5V batteries)
Output Stability	±0.05dB/15mins; ±0.1dB/ 8hours
Modulation Frequencies	CW, 270Hz, 1KHz, 2KHz
Dimensions / Weight	160x85x45mm / 220g

Product Display

