

ARC-400



产品型号 Product type	ARC-400
输入电压 Voltage	3PH380V±15%
输入频率 Input Frequency(Hz)	50/60
输出空载电压 No-load output voltage	63
额定输入功率 Rate input capacity(KVA)	13KVA
切割电流调节范围 Output current range(A)	30-400
功率因数 Power factor(COS)	0.93
占空比 Rated Duty Cycles(%)	60%
效率 Efficiency(%)	85%
防护等级 Protection grade	IP21
绝缘等级 Class of Insulation	F
焊条直径 Electrode diameter(mm)	3.2-5.0
焊接厚度 Welding thickness(mm)	2.0-15mm
裸机重量 Weight(kg)	9.5
外形尺寸 Dimensions(mm)	480*210*310



ARC-400 machine
 Include accessories:
 2m electrode holder
 2m earth clamp
 Mask
 Cinder hammer

ARC-400



产品型号 Product type	ARC-400
输入电压 Voltage	3PH380V±15%
输入频 Input Frequency(Hz)	50/60
输出空载电压 No-load output voltage	63
额定输入功率 Rate input capacity(KVA)	13KVA
切割电流调节范围 Output current range(A)	30-400
功率因数 Power factor(COS)	0.93
占空比 Rated Duty Cycles(%)	60%
效率 Efficiency(%)	85%
防护等级 Protection grade	IP21
绝缘等级 Class of Insulation	F
焊条直径 Electrode diameter(mm)	3.2-5.0
焊接材料 Welding material	Carbon steel Low alloy steel Stainless steel
焊接厚度 Welding thickness(mm)	2.0-15mm
裸机重量 Weight(kg)	9
外形尺寸 Dimensions(mm)	450*230*340



ARC-400
 Include accessories:
 2m electrode holder
 2m earth clamp
 Mask
 Cinder hammer