


POS Printer RP326

Item #		Thermal Printer RP326
Photo		
Color		Black
Print	Printing Method	Thermal Line
	Printing Speed	250mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
Character	Character Set	ANK,GB18030(Chinese)
	Print Font	ANK: 12 x24,9x17, Chinese: 24 x 24
	Character per Line	48-font A/64-font B
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5±0.5mm
	Paper Roll Diameter	Max: 80.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06 to 0.07mm
Paper Supply Method		Drop-in paper load
Reliability	MCBF	60 million lines
	Auto Cutter	500,000 cuts
	TPH	100km
Barcodes	UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128	
Emulation		ESC/POS
Driver		Windows2000/XP/7/VISTA
Sensor		Paper Near End Sensor, Paper End Sensor
Drawer Port		1 Port
Interface		RS-232, Parallel, USB, Ethernet
Power Supply (Adapter)		AC100 ~240V(± 10%) DC 24V, 2A
Auto cutter	Type	Guillotine
	Life	1,000,000 cuts
Physical	Net Weight	1.3kg
	Gross Weight	2.8kg
	Printer Dimension (WxLxH)	145 x 195x 148 mm
Application	Restaurants, Department Stores, Kitchen, Convenience Stores, Specialty Retail, Super market	