

# Huawei CloudEngine S5735I-H-V2 Series TSN Industry Switches (DIN-rail) Brochure

Huawei CloudEngine S5735I-H-V2 series TSN industry switches are standard industry switches that provide GE downlink ports and GE, 10GE SFP+ uplink ports.


## Product Overview

Huawei CloudEngine S5735I-H-V2 series TSN industry switches (S5735I-H-V2 for short) are next-generation standard Layer 3 gigabit switches that provide flexible all-gigabit access and GE/10GE uplink ports.

TSN industry switches have an industrial-grade operating temperature range as well as professional outdoor surge protection to withstand harsh outdoor environments. As such, they can be widely used in ultra-broadband operating temperature scenarios, such as smart manufacturing, smart mining, smart transportation, safe city, and electric power.

## Models and Appearances

Models and appearances of the CloudEngine S5735I-H-V2 series

Models and Appearances	Description
 <p>CloudEngine S5735I-H8T4S2XN-V2</p>	<ul style="list-style-type: none"> <li>• 8 x 10/100/1000Base-T Ethernet ports, 4 x GE SFP ports, 2 x 10GE SFP+ ports, 1 x DI/DO, 1 x RS485</li> <li>• DC external or AC adapter</li> <li>• 1+1 power supply backup</li> <li>• Forwarding performance: 48 Mpps</li> <li>• Switching capacity: 64 Gbps/520 Gbps*</li> </ul>

\*Note: The value before the slash (/) refers to the device's switching capability, while the value after the slash (/) means the system's switching capability.

## Features and Highlights

### Powerful Service Processing Capability

- CloudEngine S5735I-H-V2 supports a broad set of Layer 2/Layer 3 multicast protocols, such as PIM SM, PIM DM, PIM SSM, and IGMP snooping. This capability is ideal for high-definition video backhaul and video conferencing access.
- CloudEngine S5735I-H-V2 provides multiple Layer 3 features including OSPF, IS-IS, BGP, and VRRP, meeting enterprises' access and aggregation service needs and enabling a variety of voice, video, and data applications.

## Multiple Security Control Mechanisms

- CloudEngine S5735I-H-V2 supports MAC address authentication, 802.1X authentication, and implements dynamic delivery of policies (VLAN, QoS, and ACL) to users.
- CloudEngine S5735I-H-V2 provides a series of mechanisms to defend against DoS attacks and user-targeted attacks. DoS attacks are targeted at switches and include SYN flood, Land, Smurf, and ICMP flood attacks. User-targeted attacks include bogus DHCP server attacks, IP/MAC address spoofing, DHCP request flood, and changing of the DHCP CHADDR value.
- CloudEngine S5735I-H-V2 sets up and maintains a DHCP snooping binding table, and discards the packets that do not match the table entries. The DHCP snooping trusted port feature ensures that users connect only to the authorized DHCP server.
- CloudEngine S5735I-H-V2 supports strict ARP learning, which protects a network against ARP spoofing attacks to ensure that users can connect to the Internet normally.
- CloudEngine S5735I-H-V2 supports policy association, user permission policy management and policy execution, and user permission association switchover based on the authentication status.

## Multiple Reliability Mechanisms

- CloudEngine S5735I-H-V2 supports a single power module or two power modules. When two power modules are used, the power modules work in 1+1 backup mode. They can be directly connected to an external DC power supply or powered by a power module.
- In addition to traditional Spanning Tree Protocol (STP), Rapid Spanning Tree Protocol (RSTP), and Multiple Spanning Tree Protocol (MSTP), the CloudEngine S5735I-H-V2 supports Huawei-developed Smart Ethernet Protection (SEP) technology and the latest Ethernet Ring Protection Switching (ERPS) standard. ERPS is defined in ITU-T G.8032. It implements 20ms fast protection switching based on traditional Ethernet MAC and bridging functions.
- CloudEngine S5735I-H-V2 supports Smart Link, which implements backup of uplinks. One CloudEngine S5735I-S switch can connect to multiple aggregation switches through multiple links, significantly improving reliability of access devices.

## Easy Network deployment

- CloudEngine S5735I-H-V2 supports Huawei Easy Operation, a solution that provides zero-touch deployment, replacement of faulty devices without additional configuration, USB-based deployment, batch device configuration, and batch remote upgrade. The capabilities facilitate device deployment, upgrade, service provisioning, and other management and maintenance operations, and also greatly reduce O&M costs. CloudEngine S5735I-H-V2 can be managed using SNMP v1/v2c/v3, CLI, web-based network management system, or SSH v2.0. Additionally, it supports RMON, multiple log hosts, port traffic statistics collection, and network quality analysis, which facilitate network optimization and reconstruction.

## Mature IPv6 Technologies

- CloudEngine S5735I-H-V2 supports IPv4/IPv6 dual stack, IPv6 RIPng, BGP4+, OSPFv3.
- CloudEngine S5735I-H-V2 can be deployed on a pure IPv4 network, a pure IPv6 network, or a shared IPv4/IPv6 network, helping achieve IPv4-to-IPv6 transition.

## Network Slicing Functions

- CloudEngine S5735I-H-V2 provides a range of VLAN slicing functions to meet diversified SLA requirements of different services and customers. Service isolation and bandwidth guarantee are implemented based on QoS. Slices can be completely isolated from each other without affecting each other. Traffic is isolated at the physical layer, and network slicing is performed for services on the same physical network. The Network Slicing technology can be used at the access, aggregation, and core layers to meet differentiated SLA requirements of new services on campus networks.

## TSN Network

- CloudEngine S5735I-H-V2 provides the TSN function. Based on high-precision time synchronization and time gating scheduling (802.1Qbv), the switches provide the deterministic delay network and TSN deterministic network, which can be used in scenarios such as industrial control and motion control.

## Intelligent O&M

- CloudEngine S5735I-H-V2 provides telemetry technology to collect device data in real time and send the data to Huawei campus network analyzer CampusInsight. The CampusInsight analyzes network data based on the intelligent fault identification

algorithm, accurately displays the real-time network status, effectively demarcates and locates faults in a timely manner, and identifies network problems that affect user experience, accurately guaranteeing user experience.

## Intelligent Upgrade

- CloudEngine S5735I-H-V2 supports the intelligent upgrade feature. Specifically, CloudEngine S5735I-H-V2 obtains the version upgrade path and downloads the newest version for upgrade from the Huawei Online Upgrade Platform (HOUP). The entire upgrade process is highly automated and achieves one-click upgrade. In addition, preloading the version is supported, which greatly shortens the upgrade time and service interruption time.
- The intelligent upgrade feature greatly simplifies device upgrade operations and makes it possible for the customer to upgrade the version independently. This greatly reduces the customer's maintenance costs. In addition, the upgrade policies on the HOUP platform standardize the upgrade operations, which greatly reduces the risk of upgrade failures.

## NCE Management

- The Huawei NCE Campus management platform allows users to configure, monitor, and inspect switches on the cloud, reducing on-site deployment and O&M manpower costs and decreasing network OPEX.
- Huawei switches support both NCE Campus management and on-premise management modes. These two management modes can be flexibly switched as required to achieve smooth evolution while maximizing return on investment (ROI).

## OPS

- CloudEngine S5735I-H-V2 supports Open Programmability System (OPS), an open programmable system based on the Python language. IT administrators can program the O&M functions of a CloudEngine S5735I-H-V2 switch through Python scripts to quickly innovate functions and implement intelligent O&M.

# Licensing

CloudEngine S5735I-H-V2 supports both the traditional feature-based licensing mode, TSN Basic Function License and the latest Huawei IDN One Software (N1 mode for short) licensing mode. The N1 mode is ideal for deploying Huawei CloudCampus Solution in the on-premises scenario, as it greatly enhances the customer experiences in purchasing and upgrading software services with simplicity.

### Software Package Features in N1 Mode

Switch Functions	N1 Basic Software	N1 Foundation Software Package	N1 Advanced Software Package
<b>Basic network functions:</b> Layer 2 functions, IPv4, IPv6 and others Note: For details, see the Service Features	√	√	√
<b>Basic network automation based on the iMaster NCE-Campus:</b> <ul style="list-style-type: none"> <li>● NE management: Device management, topology management and discovery</li> <li>● User access authentication</li> </ul>	×	√	√
<b>Advanced network automation and intelligent O&amp;M:</b> IPCA, CampusInsight basic functions	×	×	√

Note: Only V600R022C01 and later versions can support N1 mode

# Product Specifications

Item	CloudEngine S5735I-H8T4S2XN-V2
Fixed port	8 x 10/100/1000BASE-T ports, 4 x GE SFP ports, 2 x 10GE SFP+ ports
Console port	1 x RS485
Alarm port	1 x DI (Monitoring alarm input port), 1 x DO (Shorts and Opens alarm output port)
Dimensions (H x W x D)	150.0 mm x 120.0 mm x 133.0 mm
Mounting	DIN rail or Rack-mounted
Weight (with packaging)	2.11kg
IP level	IP40
Power supply type	60W AC (AC power adapter) or DC external, 1:1 hot backup
Rated voltage range	<ul style="list-style-type: none"> <li>DC input: 12V DC~48V DC</li> </ul>
Maximum voltage range	<ul style="list-style-type: none"> <li>DC input: 9.6V DC~60V DC</li> </ul>
Maximum power consumption	33.8 W
Typical power consumption (30% of traffic load)	25.3 W
Operating temperature	0–1800 m altitude, industry optical modules: -40°C to +60°C (installed in the sealing cabinet) -40°C to +70°C (installed in the ventilation cabinet, with the wind speed of at least 40 LFM) -40°C to +75°C (installed in the ventilation cabinet shipped with fans running at a speed of at least 200 LFM)
Storage temperature	-40°C to +85°C
Power supply surge protection	Using DC power modules: ±4 kV in differential mode, ±2 kV in common mode
Noise under normal temperature (27°C, sound power)	Noise-free (no fans), < 30 dB(A)
Relative humidity	5% to 95%, noncondensing
Heat dissipation	Natural heat dissipation

# Service Features

Item	Description
MAC address table	IEEE 802.1d compliance
	32K MAC entries
	MAC address learning and aging
	Static, dynamic, and blackhole MAC address entries
	Packet filtering based on source MAC addresses
VLAN	4094 VLANs


Item	Description
	Voice VLAN
	MUX VLAN
	VLAN assignment based on MAC addresses, protocols, IP subnets, policies, and ports
	VLAN Stacking, VLAN mapping
Reliability	Smart Link tree topology and Smart Link multi-instance, providing millisecond-level protection switchover
	SEP
	STP (IEEE 802.1d), RSTP (IEEE 802.1w), and MSTP (IEEE 802.1s)
	ERPS (G.8032)
	BPDU protection, root protection, and loop protection
	HSR dual fed and selective receiving, 0 packet loss
	LBDT
	Y.1731
IP routing	Static route, RIPv1/v2, RIPng, OSPF, OSPFv3, ECMP, IS-IS, IS-ISv6, BGP, BGP4+, VRRP, and VRRP6
	Up to 8192 FIBv4 entries
	Up to 3072 FIBv6 entries
IPv6 features	Up to 3072 ND entries
	Path MTU (PMTU)
	IPv6 ping, IPv6 tracer, and IPv6 Telnet
Multicast	PIM DM, PIM SM, PIM SSM, PIMv6
	IGMP v1/v2/v3, IGMP v1/v2/v3 snooping, MLD snooping and IGMP fast leave
	Multicast load balancing among member ports of a trunk
	Port-based multicast traffic statistics
	Multicast VLAN
TSN	IEEE 802.1Qbv, $\mu$ s-level deterministic latency
Industrial Agreement	Profinet RT, Ethernet/IP, Modbus TCP, OPC UA and GOOSE mainstream industrial protocol forwarding
	IEEE 1588v2 clock synchronization
QoS/ACL	Rate limiting on packets sent and received by a port
	Packet redirection
	Port-based traffic policing and two-rate three-color CAR
	Eight queues on each port
	DRR, SP and DRR+SP queue scheduling algorithms
	Re-marking of the 802.1p priority and DSCP priority
	Packet filtering at Layer 2 to Layer 4, filtering out invalid frames based on the source MAC address, destination MAC address, source IP address, destination IP address, TCP/UDP port number, protocol type, and VLAN ID

Item	Description
	Rate limiting in each queue and traffic shaping on ports
	Profinet RT, Ethernet/IP, Modbus TCP, and OPC UA mainstream industrial protocol forwarding
	Network Slicing (VLAN)
Security	Hierarchical user management and password protection
	DoS attack defense, ARP attack defense, and ICMP attack defense
	Binding of the IP address, MAC address, port number, and VLAN ID
	Port isolation, port security, and sticky MAC
	Blackhole MAC address entries
	Limit on the number of learned MAC addresses
	IEEE 802.1x authentication and limit on the number of users on a port
	AAA authentication, RADIUS authentication, HWTACACS authentication, and NAC
	SSH v2.0
	HTTPS
	CPU defense
	Blacklist and whitelist
	IEEE 802.1x authentication, MAC address authentication
	DHCPv4 client/relay/server/snooping
	DHCPv6 client/relay
	Attack source tracing and punishment for IPv6 packets such as ND, DHCPv6
	ND snooping
	policy association
Management and maintenance	NCE Campus management based on Netconf/Yang
	Virtual cable test
	SNMP v1/v2c/v3
	RMON
	Web-based NMS
	System logs and alarms of different levels
	802.3az EEE
	1588v2
	Registration Center Deployment
	GVRP
	iPCA、sFlow、NQA、Telemetry
Interoperability	Supports VBST (Compatible with PVST/PVST+/RPVST)

# Networking and Applications


## Video surveillance application, outdoor cabinet

CloudEngine S5735I-H-V2 series switches supports extended operating temperature range, with professional surge protection capabilities, suitable for outdoor environment. CloudEngine S5735I-H-V2 series switch can be used for safe city scenario to provide remote access for the camera.




## ETTx scenario

CloudEngine S5735I- series switches supports extended operating temperature and provides GE access and 10GE uplinks for ETTx access scenarios.




## Deterministic Latency scenario

CloudEngine S5735I- series switches supports extended operating temperature and provides GE access and 10GE uplinks for ETTx access scenarios.



## Power Specifications

Specification	60W Power Module
Models and Appearances	
Power specifications	<ul style="list-style-type: none"> <li>Rated input voltage range:           <ul style="list-style-type: none"> <li>100 V AC to 240 V AC, 50/60 Hz</li> <li>100V DC to 250 V DC</li> </ul> </li> <li>Rated output voltage:           <ul style="list-style-type: none"> <li>12 V DC</li> </ul> </li> </ul>
Power	60 W
Weight	0.9 kg
Dimensions (H x W x D)	40 mm x 150 mm x 133 mm
Storage temperature	-40°C to +85°C
Operating temperature	-40°C to +70°C
Installation mode	Installed on the DIN rail
Operating humidity	5% to 95% (non-condensing)

## Ordering Information

Module	Description
CloudEngine S5735I-H8T4S2XN-V2	CloudEngine S5735I-H8T4S2XN-V2 (8*10/100/1000BASE-T ports, 4*GE SFP+ ports, 2*10GE SFP+ ports, DIN Rail Mounting, Dual redundant 9.6 to 60V DC power, Fanless)
PAC60S12-AN	Industrial 60 W AC power module, DIN RAIL
N1-S57H-M-Lic	S57XX-H Series Basic SW, Per Device
N1-S57H-M-SnS1Y	S57XX-H Series Basic SW, SnS, Per Device, 1Year
N1-S57H-F-Lic	N1-CloudCampus, Foundation, S57XX-H Series, Per Device
N1-S57H-F-SnS1Y	N1-CloudCampus, Foundation, S57XX-H Series, SnS, Per Device, 1Year
N1-S57H-A-Lite-Lic	N1-CloudCampus, Advanced-Lite, S57XX-H, Per Device
N1-S57H-A-Lite-SnS-3Y	N1-CloudCampus, Advanced-Lite, S57XX-H, SnS, Per Device, 3 Year
N1-S57H-FToA-Lite-Lic	N1-Upgrade-Foundation to Advanced-Lite, S57XX-H, Per Device
N1-S57H-FToA-Lite-SnS-3Y	N1-Upgrade-Foundation to Advanced-Lite, S57XX-H, SnS, Per Device, 3 Year



Module	Description
L-TSN-S571H	TSN Basic Function License, Per Device

## More Information

For more information about Huawei Campus Switches, visit <http://e.huawei.com> or contact us in the following ways:


- Global service hotline: <http://e.huawei.com/en/service-hotline>
- Logging in to the Huawei Enterprise technical support website: <http://support.huawei.com/enterprise/>
- Sending an email to the customer service mailbox: [support\\_e@huawei.com](mailto:support_e@huawei.com)

---

**Copyright © Huawei Technologies Co., Ltd. 2024. All rights reserved.**

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

### Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

### Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

### Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base Bantian,  
Longgang Shenzhen 518129 People's  
Republic of China

Website: [e.huawei.com](http://e.huawei.com)