

GLK 3500

# Optical Time Domain Reflectometer



**3.5 inch**  
3.5 inch Color LCD



**9**  
9 Functional Modules

**24 dB**  
24 dB Dynamic Range

**iLNM-EVENT MAP**

**Fiber & RJ45**  
Photoelectric Integration  
Multi-Functions

*Make a product, win the world's admiration*





24dB Dynamic Range  
80km Precision Test  
Online Detection -APD Effective Protection  
2.5m Event Blind Zone



OTDR Optical Time Domain Reflectometer  
OPM -50~+26dBm Optical Power Meter  
VFL Visual Fault Locator  
LS Stabilized Light Source  
RJ45 Ethernet Cable Sequence



Dual-wavelength OTDR  
iLOM-Event Map  
RJ45 Cable Length Measurement  
RJ45 Line-Tracker Function



One-click Automatic Test  
File Auto-saving  
Test Results Automatic Analysis



SOR File Batch Processing  
Remote Upgrade  
Batch Export of USB Data Files



12h Continuous measurement time  
20h Super-long Standby  
Working Temperature: -10°C ~ +50°C

## Technical Specifications

OTDR					
Model	D	F1	F2	T	P1F1
Wavelength	1310/ 1550nm	1310nm	1550nm	1610nm	1625nm
Fiber Type	G.652				
Dynamic Range	24/22dB	24dB	22dB	22dB	22dB
Event Blind Zone	2.5m				
ATT Blind Zone	8m				
Test Range	500m~128km				
Pulse Width	3ns~10us				
Ranging accuracy	± (1m+ Sampling interval +0.005%×Test distance)				
Loss accuracy	±0.2dB/dB				
Sampling Points	16k~128k				
Sampling resolution	0.05m~8m				
Reflection accuracy	±3dB				
Data Storage	Internal: ≥600; External: TF Card				
Laser Safety Level	Class II				
File format	SOR Standard file format				
Connector	FC/UPC (Interchangeable SC、ST)				
OPM					
Wave Range	800nm~1700nm				
Interface Type	Universal Joint FC/SC/ST				
Test Range	-50dBm~+26dBm				
Uncertainty	±5%				
Frequency Identification	CW/270/330/1k/2kHz				
Calibration wavelength	850/980/1300/1310/1490/1550/1625/1650nm				

LS	
LD Type	FP-LD
Wavelength	Consistent with OTDR output wavelength
Output Power	≥-5dBm
Modulation Frequency	270/330/1k/2kHz
Stability	CW, ±0.5dB/15min (Test after 15 minutes of preheating)
Connector	FC/UPC (Interchangeable SC、ST)
VFL	
Wavelength	650nm±20nm
Output Power	≥10mW
Mode	CW/1Hz/2Hz
Connector	FC/SC/ST
RJ45 Cable Length Measurement	
Test Range	300m
Other Parameters	
Display	Toughened glass, 3.5 inch Color LCD
Data Interface	Micro USB
External storage	TF Card
Power Supply	Polymer Li-Battery: 3.7V, 4000mAh Adapter: 5VDC, 2A
Battery Life	Standby>20h; Measuring time>12h
Operating Temperature	-10°C~+50°C
Storage Temperature	-40°C~+70°C
Relative Humidity	0~95%Non Condensing
Size	173mm×82mm×37mm
Weight	≤350g